

MARATHON MaxiLog™

Our Single-use Temperature Logger with Real-Time LCD Display for Instant TOA (Time Over Alarm) Conditions.

MaxiLog is the revolutionary, single-use, pre-programmed, electronic temperature data recorder specifically designed for measuring temperatures during the transportation of refrigerated vaccines, biological material, chemicals, pharmaceuticals, and for documenting the transportation of perishable commodities. The real-time LCD screen provides instant TOA (Time Over Alarm) notification.

The MaxiLog is NIST-traceable and available with Certificates of Temperature Conformance.

Functions include:

- Internal Thermistor: accurately records time and temperatures for user selectable readings in Celsius or Fahrenheit.
- LCD display: Shows High and Low Alarm Limits, Current Temperature, Run Time and TOA (Time Over Alarm) in Days, Hours and Minutes.

Small Form Factor: The internal software records the following: time mechanism, start time, sampling intervals, end description for special instructions, alarm values, recording status, measurement data, software version, serial and tracking number, model type, and after the fact report generation options.

Visual Alarms: All our data loggers can be programmed with alarm limits. Should the temperature reach levels outside these limits, the LDC will display an alarm icon. To start the recorder, simply press the start button!



Temperature Range

- -35°C to +50°C
(-31°F to +122°F)

Temperature Accuracy

- ±0.2°C (±0.36°F)
from 0° to 10° C
(30° to 50° F);
±1.0°C (±1.8°F)
at extremes

Measurement Intervals

2 seconds to months

Number of Measurements


8K memory

MARATHON
PRODUCTS, INC.



Don't ship without us!®

MaxiThermal Software Highlights: Easy-to-use software provides clear graphs. Report Summary & Statistics File Manager, Note Attachment, Zoom, Elapsed Time or Date/Time View, Recorded View, Celsius or Fahrenheit. Data can be exported to other Windows programs such as spreadsheets, word-processing or databases. Available for Windows XP, Vista 7, 8 and 10. An Enterprise Software version and 21CFR Part 11 Compliant Software are also available.



MaxiThermal Temperature Plots and Summary Information window.

Serialization:

This recorder is programmed at the factory with a unique serial number for positive tracking.

Water-resistant Enclosure:

The product package is hermetically sealed to an IP66 rating.

Recyclable:

Single-Use MaxiLog units are designed for single use, and we encourage recycling. Please call Marathon Products for complete disposal or recycling instructions.

Minimum Order Quantity:

Single-Use MaxiLog units are sold in minimum lot quantities of 25 units. Your order is shipped on the same day if the order is placed before 2 p.m. PST.

Options:

- MaxiThermal software
- USB cradle

USB Interface: To download recorded information, simply plug the USB Cradle into the standard USB port of your PC.

Computer Ready: MaxiThermal software is used to read the logger. It runs on Windows XP, Vista, 7, 8 and 10. The MaxiThermal software and USB Cradle are available as separate accessory items.

MaxiLog Specifications SKU #7029

- Memory EEPROM, Storage: EEPROM, 8k Storage (approx. 8,000 data points)
- Temperature Range: -35°C to +50°C (-31°F to +122°F)
- Temperature Accuracy: ±0.2°C at 0° to 10°C, ±1.0°C at extremes (±0.36°F at 32° to 50° F, ±1.8°F at extremes)
- Measurement Intervals: Pre-programmed from 2 seconds to hours depending on model type (duration).
- Temperature Sensor: NIST-traceable Precision SMT Thermistor
- Indicators: LCD Display. Start/Stop and Alarm
- High and low alarm limits: Alarm set by temperature and time
- Computer Interface: USB Cradle
- Internal firmware Provides: Times, Start time, Interval, User description, Alarm values, Recording status, Measurement data, Firmware version, Serial number, Model type
- Power Source: Lithium Battery (2 year operating, 3 year shelf life)
- Size:
 - Length: 5.5 cm (2.2 in.)
 - Width: 2.7 cm (1.0 in.)
 - Depth: 1.4 cm (0.55 in.)
- Weight: 19 g (.67 oz.)

Please call 1-510-562-6450
for more information or to place an order.

www.marathonproducts.com

14500 Doolittle Drive, San Leandro, CA 94577 ■ jnakagawa@marathonproducts.com

Specifications subject to change without prior notice.



USB cradle